V7 ULTRA-THIN HDMI® CABLE WITH ETHERNET 3m

Key Features

- Redmere® technology boosts signal strength allowing for a thinner longer cable and up to 10.2 GBps data throughput
- Ultra-thin cable makes it easy to route around corners and walls
- Directional, supports 4K resolution up to 3840 x 2160 pixels and digital 7.1 surround sound
- Gold-plated connectors and contacts help ensure maximum signal transfer and corrosion resistance

V7HD4S-03M-1E

Overview

Designed with Redmere® technology, that boosts the digital video and digital audio signal, allowing for a thinner cable that is easier to route in tight spaces and long runs. The V7 ultra-thin HDMI cables are 50% thinner than standard HDMI cables, delivering up to 3840 x 2160 resolution and digital 7.1 surround sound through a single cable. The gold plated contacts and connectors provide maximum signal transfer and corrosion resistance. These cables deliver Ethernet data interconnectivity for compatible devices and are fully backward compatible with older HDMI-capable devices.

Specification

V7 Model #	V7HD4S-03M-1E
IM SKU #	J152404
EAN	0662919069631
Cable length	3 meter
Color	Black
Compatibility	Audio/Video Device,TV, Gaming Console, Projector, Blu-Ray Disc™ players, HDTVs, DVD Players, DVRs, set-top boxes, DTV, DVD stereo receivers and more.
Compliance	ROHS
Connector 1	1 x 19-pin Type HDMI Male (gold plated)
Connector 2	1 x 19-pin Type HDMI Male (gold plated)
Country of Origin	China
Package dim. (L/W/H)	160 x 134 x 17 mm
Package Weight	90.7 g
Packaging type	Retail package with hangtag
Product dim. (L/W/H)	3000 x 20 x 16 mm
Product Type	HDMI
Product Weight	27 g
Warranty	2 years

The data in this publication is for illustration purposes only and does not necessarily represent standards or specifications which must be met by V7. Design and specifications are subject to change without prior notice. Trademarks belong to their respective owners. No responsibility assumed and all liability for damages resulting from use of this information or for any errors or omissions, are disclaimed. Measurement standards and testing conditions, as per manufacturer definitions, are available on request.